System Section "Solar Green Roof Optigrün Solar FKD"

Variant: Optigrün-Solar FKD
Orientation: East-West + Portrait
Example: PV modul 1762 mm x 1134 mm



Optigrün Solar FKD 15°

- Base Plate for Optigrün Solar FKD
- Mounting Frame 15° for Optigrün Solar with Rail Fixings
- PV module
- Easy Mounting Rail with Module Clamps

H_{bo} 10°	H_{bo} 15°	H_{bo} 20°
628	718	813

Economy Roof

- vegetation
- Optigrün Extensive Substrate min. 60 mm (higher loads may be necessary for the required ballasting)
- Optigrün Filter Fleece FIL150
- Optigrün Drainage and Storage Board FKD 25
- Optigrün Protection and Storage Fleece RMS 500
- Waterproofing membrane (root resistant according to FLL)*
- Suitable substructure*

* According to national regulations *** other clamping distances possible with Vario rail

OPTIGRÜN® ROOF GREENING

The depicted solution is intended for use with green roof systems. Other construction tradework is simplified in this representation and should be constructed according to current industry standards. Optigrün reserves the right to make changes to its product solutions.

Approved:	com		drawn by:	scale:	update:	Rev.:	Detail-No.:
LC, LG		O	MH	not to scale	23.10.25	4	SOL-22_2.1200_UgD

Reprinting is only permitted with the prior permission of the editors. No responsibility for printing errors. Subject to technical modifications.

Dateiname: SOL-22_2.1200_UgD____O-W-P.vwx